

**Listing of Claims**

1. (Currently Amended) ~~An accessory for a line trimmer that includes a main pole with a trimmer head attached at one end, said accessory~~ A constant height adjustable line trimmer, comprising:

a. a line trimmer including a main pole, a handle attached to one end of said main pole, and a trimmer head attached to the end of the main pole opposite said handle, said trimmer head including a rotating line capable of cutting vegetation;

a.b. ~~an~~ a short extension arm having a distal end and a proximal end;

b.c. a wheel assembly attached to said distal end of said extension arm, said wheel assembly including at least one wheel rotatably mounted thereon; and,

e.d. a first clamp member used to longitudinally align and attach said extension arm to a said main pole of a on said line trimmer so that said distal end of said extension arm extends forward from the trimmer head, said first clamp member able to move longitudinally over said main pole and be attached at different positions to the main pole thereby allowing said wheel assembly to be positioned in front of said trimmer head at different distances to support said trimmer head at different desired angles and elevations above a support surface when said handle is held and said line trimmer is pushed or pulled over a support surface. and  
~~the distance between the trimmer head and said wheel assembly to be adjusted thereby allowing the trimmer head to be positioned at different heights for cutting vegetation at a constant height when the wheel assembly is rolled over a support surface~~

2. (Currently Amended) The line trimmer ~~accessory~~, as recited in Claim 1, further including said wheel assembly being rotatably attached to said distal end of said extension arm and a

1 locking means for selectively locking said wheel assembly in a desired position on said  
2 extension arm.

3  
4 3. (Currently Amended) The line trimmer accessory, as recited in Claim 1, further including  
5 a second clamp member attached to said extension arm that enables the length of said  
6 extension pole between said first clamp member and said wheel assembly to be adjusted  
7 thereby allowing the pitch of said extension arm relative to the main pole to be adjusted.

8  
9 4. (Currently Amended) The line trimmer accessory, as recited in Claim 3, further including  
10 said wheel assembly being rotatably attached to said distal end of said extension arm and a  
11 locking means for selectively locking said wheel assembly in a desired position on said  
12 extension arm.

13  
14 5. (Currently Amended) The line trimmer accessory, as recited in Claim 3, wherein said first  
15 and second clamp members are formed on a rotating L-shaped bracket selectively attaching  
16 said extension arm to the main pole, said L-shaped bracket includes a first support flange that  
17 supports said first clamp member and a second support flange that supports said second  
18 clamp member, said first support flange and said second support flange being perpendicularly  
19 aligned thereby perpendicularly aligning said first clamp member and said second clamp  
20 member

21  
22 6. (Currently Amended) The line trimmer accessory, as recited in Claim 5, further including  
23 said wheel assembly being rotably attached to said distal end of said extension arm and a

1 locking means enabling said wheel assembly to be selectively locked in a desired position on  
2 said extension arm.

3  
4 7. (Currently Amended) The line trimmer accessory, as recited in Claim 1, wherein said first  
5 clamp member includes an upper clamp member, a lower clamp member, a center post, a  
6 pivoting handle attached to said post, and a strap, said upper and lower clamp members  
7 including teeth that selectively engage when said upper and lower clamp members are forced  
8 together, said strap member extending through said lower clamp member and wrapped  
9 around a main pole on a line trimmer, said center post extending through said upper clamp  
10 member and connecting to said strap to connect said upper clamp member and said lower  
11 clamp member together and to tighten said strap around the main pole.

12  
13 8. (Previously Amended) An accessory for a line trimmer that includes a main pole with a  
14 trimmer head attached at one end, said accessory comprising:

- 15 a. ~~an~~ a short extension arm having a distal end and a proximal end;
- 16 b. a wheel assembly attached to said distal end of said extension arm, said wheel  
17 assembly including at least one wheel mounted thereon;
- 18 c. a an adjustable first clamp member attached to said proximal end of ~~used to~~  
19 ~~longitudinally align and attach~~ said extension arm ~~to a main pole of a line trimmer~~, said first  
20 clamp member capable of being selectively attached to a main pole on a line trimmer to  
21 connect said extension arm to the main pole, said first clamp member being adjustable along  
22 said extension arm so that ~~said enabling the length~~ distance between ~~of~~ said wheel assembly  
23 and a trimmer head attached to the main pole may be adjusted to support the trimmer head at

1 different angles and elevations ~~position extension arm between the trimmer head and said~~  
2 ~~wheel assembly to be adjusted for supporting a trimmer head at different elevations when the~~  
3 main pole is held and said wheel is rolled across a support surface.

4 d. a second clamp member attached to said extension arm that enables the  
5 angular orientation of said extension arm to be adjusted relative to the main pole on a the line  
6 trimmer; and,

7 e. a locking member attached to said wheel assembly enabling said wheel  
8 assembly to be selectively locked in position on said extension arm.

9  
10 9. (Original) The accessory, as recited in Claim 8, wherein said first and second clamp  
11 members are formed on a rotating L-shaped bracket selectively attaching said extension arm  
12 to the main pole, said L-shaped bracket includes a first support flange that supports said first  
13 clamp member and a second support flange that supports said second clamp member, said  
14 first support flange and said second support flange being perpendicularly aligned.

15  
16 10. (Original) The accessory, as recited in Claim 8, wherein said first clamp member includes  
17 an upper clamp member, a lower clamp member, a center post, a pivoting handle attached to  
18 said post, and a strap, said upper and lower clamp members including teeth that selectively  
19 engage when said upper and lower clamp members are forced together, said strap member  
20 extending through said lower clamp member and wrapped around a main pole on a line  
21 trimmer, said center post extending through said upper clamp member and connecting to said  
22 strap to connect said upper clamp member and said lower clamp member together and to  
23 tighten said strap around the main pole.

1 11. (Original) The accessory, as recited in Claim 9, wherein said first clamp member  
2 includes an upper clamp member, a lower clamp member, a center post, a pivoting handle  
3 attached to said post, and a strap, said upper and lower clamp members including teeth that  
4 selectively engage when said upper and lower clamp members are forced together, said strap  
5 member extending through said lower clamp member and wrapped around a main pole on a  
6 line trimmer, said center post extending through said upper clamp member and connecting to  
7 said strap to connect said upper clamp member and said lower clamp member together and to  
8 tighten said strap around the main pole.

9  
10 12. (Original) The accessory, as recited in Claim 8, wherein said wheel is rotatably mounted  
11 on said wheel assembly.

12  
13 13. (Original) The accessory, as recited in Claim 8, wherein said wheel assembly is fixed in  
14 position on said extension pole.